

Requested Patent: EP0951886A1

Title: DISPOSABLE DIAPER ;

Abstracted Patent: EP0951886 ;

Publication Date: 1999-10-27 ;

Inventor(s): SASAKI TORU (JP) ;

Applicant(s): UNI CHARM CORP (JP) ;

Application Number: EP19990303059 19990420 ;

Priority Number(s): JP19980109960 19980420 ;

IPC Classification: A61F13/15 ;

Equivalents:

AU2383199, AU751137, BR9902190, CA2269452, CN1234217, DE69918591D,
DE69918591T, ID22464, JP11299826, JP3330076B2, SG73630, US6238380 ;

ABSTRACT:

In a disposable diaper, a topsheet 2 covering a top surface 17 of a liquid-absorbent core 4 is folded along side edges of the core 4 so as to cover a bottom surface 18 of the core 4. On the bottom surface 18 of the core 4, the topsheet 2 is bonded to a backsheet 3 along zones respectively spaced from side edges 22A, 22B of the core 4 towards a center line C-C of the diaper. Elastic members 37 provided in association with leg-openings are secured to the backsheet 3 in vicinity of the respective side edges 22A, 22B of the core.

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 951 886 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.10.1999 Bulletin 1999/43

(51) Int Cl.⁶: **A61F 13/15**

(21) Application number: 99303059.2

(22) Date of filing: 20.04.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 20.04.1998 JP 10996098

(71) Applicant: **UNI-CHARM CORPORATION**
Kawanoe-shi Ehime-ken (JP)


(72) Inventor: **Sasaki, Toru,**
c/o Research & Development Division
Mitoyo-gun, Kagawa-ken 769-1602 (JP)

**(74) Representative: Parry, Christopher Stephen
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Herts. WD1 7HE (GB)**

(54) Disposable diaper

(57) In a disposable diaper, a topsheet 2 covering a top surface 17 of a liquid-absorbent core 4 is folded along side edges of the core 4 so as to cover a bottom surface 18 of the core 4. On the bottom surface 18 of the core 4, the topsheet 2 is bonded to a backsheet 3

along zones respectively spaced from side edges 22A, 22B of the core 4 towards a center line C-C of the diaper. Elastic members 37 provided in association with leg-openings are secured to the backsheet 3 in vicinity of the respective side edges 22A, 22B of the core.



EP 0 951 886 A1

Description

[0001] This invention relates to disposable 'diapers for absorbing and containing body exudates.

[0002] Japanese Patent Publication No. Sho52-40267 discloses a disposable diaper comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between these two sheets. The topsheet and the backsheet are bonded together along their portions extending outwards beyond a peripheral edge of the core. The known diaper is provided in proximity of its transversely opposite side edges with elastic members extending longitudinally of the diaper so that the lines along which these elastic members are stretched and contracted should be spaced from respective side edges of the core at least by 1.91 cm.

[0003] According to the disclosure of the Japanese Patent Publication No. Sho52-40267, the elastic members provided in association with leg-openings are spaced from the respective side edges of the core by 1.91 cm or more so that these elastic members may be free from a restriction by the core of a relatively high rigidity. According to such disclosure, it will be desired to further enlarge the distance by which the elastic members should be spaced from the respective side edges of the core as a rigidity of the core increases. However, a width of the crotch region of the diaper may be unacceptably enlarged as the distance is enlarged.

[0004] In view of the problem as has been described above, it is an object of the present invention to provide a disposable diaper allowing the elastic members associated with the leg-openings to be stretchable and contractile freely from any restriction by the rigidity of the core.

[0005] According to the invention, there is provided a disposable diaper comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between the topsheet and the backsheet which define a front waist region, a rear waist region and a crotch region extending between the front waist region and the rear waist region, and elastic members associated with leg-openings longitudinally extending along transversely opposite side edges of the diaper from the crotch region into the front and rear waist regions, wherein:

the core extends across the crotch region into the front and rear waist regions and has a top surface facing a body side of a wearer, a bottom surface opposed to the top surface, longitudinally opposite ends extending circumferentially of the diaper and transversely opposite side edges extending longitudinally of the diaper; the topsheet covering the top surface of the core is folded along the side edges of the core onto the bottom surface of the core so as to cover the bottom surface at least partially; the backsheet underlies the sections of the topsheet

folded onto the bottom surface of the core and extends outwards beyond the side edges of the core; the sections of the topsheet folded onto the bottom surface of the core are bonded to the backsheet along zones extending, inside the side edges of the core, in parallel to a center line dividing a width of the diaper in two halves; and the elastic members associated with the leg-openings are secured to the backsheet in vicinity of the side edges of the core.

[0006] According to one embodiment of the present invention, the elastic members associated with the leg-openings respectively lie in the crotch region of the diaper within a range corresponding to a width defined by 10 mm as measured inwardly from the side edges of the core plus 30 mm as measured outwardly from the lateral surfaces.

[0007] According to another embodiment of the present invention, the backsheet is formed on its inner surface with a pair of barrier cuffs each having a relatively deformable distal edge extending longitudinally of the diaper inside each of the side edges of the core, a proximal edge fixed to the inner surface of the backsheet outside or inside the side edge of the core and extending in parallel to the distal edge, and an elastic member secured to the distal edge along an apex thereof under tension given longitudinally of the diaper so that the barrier cuff is normally biased by the tension to rise on the inner surface of the backsheet.

Fig. 1 is a perspective view showing a disposable diaper according to the present invention as partially broken away;

Fig. 2 is a sectional view taken along line II-II in Fig. 1;

Fig. 3 is a view similar to Fig. 2 showing another embodiment of the present invention;

Fig. 4 is a view similar to Fig. 2 showing still another embodiment of the present invention; and

Fig. 5 is a sectional view taken along line V-V in Fig. 4.

[0008] Details of a disposable diaper according to the present invention will be more fully understood from the description given hereunder with reference to the accompanying drawings.

[0009] Diaper I shown by Fig. 1 in a perspective view as partially broken away comprises a liquid-pervious topsheet 2, a liquid-absorbent core 4 covered with the topsheet 2 and an hourglass-shaped liquid-impervious backsheet 3. The diaper 1 has a front waist region 6, a rear waist region 7 and a crotch region 8 extending between the front and rear waist regions 6, 7.

[0010] The core 4 is formed by a liquid-absorbent material 11 comprising a mixture of fluff pulp and superabsorptive polymer particles. The liquid-absorbent material 11 is covered with a tissue paper 12 and extends across the crotch region 8 into the front and rear waist

regions 6, 7. The core 4 is substantially rectangular or hourglass-shaped and defined by a top surface 17 facing a body side of a wear, a bottom surface 18 opposed to the top surface 17 (See Fig. 2), longitudinally opposite ends 21A, 21B extending circumferentially of the diaper 1, and transversely opposite side edges 22A, 22B extending longitudinally of the diaper 1.

[0011] The topsheet 2 covers the top surface 17 of the core 4 and is folded along the side edges 22A, 22B onto the bottom surface 18 so as to extend inwards transversely of the core 4 until transversely opposite side edges of the topsheet 2 thus folded are overlapped each other in proximity of a center line C-C of the core 4 (See Fig. 2). Both sections of the topsheet 2 covering the top and bottom surfaces 17, 18 of the core 4, respectively, longitudinally extend beyond the longitudinally opposite ends 21A, 21B of the core 4 so as to be placed upon and bonded to each other along their respective extensions.

[0012] The backsheet 3 is provided in the form of a laminate sheet which comprises an inner layer sheet 28 made of a liquid-impervious plastic film and an outer layer sheet 29 made of a nonwoven fabric bonded to the inner layer sheet 28 by means of adhesive 10 (See Fig. 1). The backsheet 3 underlies the sections of the topsheet 2 folded onto the bottom surface of the core 4. The backsheet 3 extends outwards beyond the longitudinally opposite ends 21A, 21B as well as beyond the transversely opposite side edges 22A, 22B of the core 4 to form longitudinally opposite ends 31A, 31B extending circumferentially of the diaper 1 and transversely opposite side edges 32A, 32B extending longitudinally of the diaper 1. The rear end 31B and the side edges 32A, 32B are provided with elastic members 36 associated with a waist-opening and elastic members 37, 37 associated with a pair of leg-openings, respectively. These elastic members 36, 37, 37 are disposed between the inner and outer layer sheets 28, 29 and secured to an inner surface of at least one of the inner and outer layer sheets 28, 29. A pair of tape fasteners 38, 38 are attached to the backsheet 3 in proximity of its respective side edges 32A, 32B of the rear waist region 7.

[0013] Fig. 2 is a sectional view taken along line II-II in Fig. 1. The bottom surface 18 of the core 4 covered with the topsheet 2 is bonded in its central zone to the backsheet 3 by means of adhesive 39, leaving the remaining zones extending in vicinity of its side edges 22A, 22B free so that a gap 41 may be formed between the bottom surface 18 and the backsheet 3. Longitudinally of the diaper 1, a zone applied with the adhesive 39 extends continuously or intermittently to the front and rear ends 21A, 21B of the core 4, or to points in vicinity thereof. Transversely of the crotch region 8, a zone applied with the adhesive 39 is spaced from each of the side edges 22A, 22B of the core 4 by a distance L which is preferably 15 mm or longer, more preferably 20 mm or longer. Transversely of the crotch region 8 again, the elastic member, 37 associated with each leg-opening

lies within a range corresponding to a width defined by 10 mm as measured inwardly from each of the side edge 22A, 22B of the core 4 towards the center line C-C of the diaper 1 plus 30 mm as measured outwardly from each of the side edge 22A, 22B. In proximity of the front and rear ends 21A, 21B of the core 4, it is also possible to bond the core 4 over its full width to the backsheet 3 with the topsheet 2 disposed therebetween.

[0014] The diaper 1 of such an arrangement allows the elastic members 37, 37 associated with the pair of leg-openings to be stretchable and contractile freely from any restriction by a rigidity of the core 4. Accordingly, the elastic members 37, 37 associated with the pair of leg-openings may be placed adjacent the core 4 to prevent excretion from leaking sideways even if the core 4 is of a relatively high rigidity. This allows, in turn, a width of the crotch region 8 to be sufficiently restricted to obtain a good feeling to wear the diaper 1. With this diaper 1, on the other hand, body fluids can be absorbed by the core 4 through its bottom surface also and therefore the effective surface area of the core 4 for direct absorption of body fluids is substantially larger than the conventional diaper adapted to absorb most of body fluids by the core through its top surface and side edges. In this way, an absorption rate of the core can be correspondingly improved.

[0015] Fig. 3 is a view similar to Fig. 2 showing another embodiment of the present invention. In the case of this diaper 1, the side sections 2A, 2A of the topsheet 2 folded onto the bottom surface of the core 4 are bonded by means of the adhesive 39 to the backsheet 3 without being overlapped each other. The elastic members 37 associated with the leg-openings lie inside as well as outside the respective side edges 22A, 22B of the core 4. The elastic members 37A lying inside the respective side edges 22A, 22B function to press the core 4 against the wearer's skin.

[0016] Fig. 4 is a view similar to Fig. 1 showing another embodiment of the present invention and Fig. 5 is a sectional view taken along line V-V in Fig. 4. This diaper 1 is provided along the transversely opposite side edges 32, 32 with a pair of barrier cuffs 46, 46 extending from the crotch region 8 into the front and rear waist regions 6, 7. Each of the barrier cuffs 46 is made of a nonwoven fabric, preferably of a substantially liquid-impervious nonwoven fabric, more preferably of a breathable but liquid-impervious nonwoven fabric. The barrier cuff 46 is bonded to the inner surface of the backsheet 3 by means of adhesive 52 and has a proximal edge 47 extending longitudinally of the diaper 1, a distal edge 49 extending in parallel to the proximal edge 47 and provided with an elastic member 48 bonded to the distal edge 49 under longitudinal tension, and an intermediate region 51 extending between these two edges 47, 49. The proximal edge 47 may be bonded to the backsheet 3 along a zone lying inside or outside, preferably inside each of the side edge 22A, 22B of the core 4. In the case of the embodiment shown in Fig. 5, the proximal edge

47 lies inside the side edge 23 of the core 4 so that a pocket 53 is formed between the barrier cuff 46 and the bottom surface 18 of the core 4. During storage of the diaper 1, front and rear ends 56, 57 of the barrier cuff 46 are collapsed outwardly or inwardly of the diaper 1 and, in their collapsed states, bonded to the topsheet 2 and/or the backsheet 3. Fig. 4 shows the case in which these front and rear ends 56, 57 of the barrier cuff 46 are collapsed inwardly of the diaper 1. Being put on the wearer's body, the diaper 1 is longitudinally curved with the core 4 inside and the elastic member 48 contracts. Thereupon, the barrier cuff 46 rises on an inner surface of the diaper 1 as indicated by imaginary lines in Fig. 5. While body fluids discharged on the diaper 1 partially flow sideways, they are prevented by the barrier cuff 46 from further flowing sideways. Body fluids thus obstructed by the barrier cuff 46 are forced to flow along the barrier cuff 46 towards the bottom surface 18 of the core 4 and absorbed by the core 4 first through the section of the topsheet 2 covering the bottom surface 18 of the core 4 and then through the bottom surface 18. The present embodiment of the diaper 1 enables body fluids to flow towards the bottom surface 18 of the core 4 more reliably than with the embodiment shown in Fig. 1.

[0017] To exploit the present invention, the topsheet 2 may be made of a nonwoven fabric or an apertured plastic film. The respective members of the diaper 1 may be bonded together using a suitable adhesive agent such as hot melt adhesive. For the members of hot melt type, the heat-sealing technique may be utilized.

[0018] With the disposable diaper according to the present invention, the elastic members secured to the backsheet in association with the leg-openings are stretchable as well as contractile freely from any restriction by the liquid-absorbent core, since the side edges of the core are spaced from the backsheet. Accordingly, the width of the crotch region can be limited as desired as possible, since the elastic members associated with the leg-openings can be placed adjacent the side edges of the core even if the core is of a relatively high rigidity.

[0019] Furthermore, the present invention enables body fluids discharged on the diaper to be partially absorbed through the bottom surface of the core so that not only an absorption rate of the core can be improved but also an amount of body fluids collected in vicinity of the core can be rapidly absorbed by the core to avoid a sideways leakage of body fluids.

Claims

1. A disposable diaper comprising a liquid-pervious topsheet, a liquid-impervious backsheet and a liquid-absorbent core disposed between said topsheet and said backsheet which define a front waist region, a rear waist region and a crotch region extending between said front waist region and said rear waist region, and elastic members associated

with leg-openings longitudinally extending along transversely opposite side edges of said diaper from said crotch region into said front and rear waist regions, wherein:

said core extends across said crotch region into said front and rear waist regions and has a top surface facing a body side of a wearer, a bottom surface opposed to said top surface, longitudinally opposite ends extending circumferentially of said diaper and transversely opposite side edges extending longitudinally of said diaper; said topsheet covering said top surface of said core is folded along said side edges of said core onto said bottom surface of said core so as to cover said bottom surface at least partially; said backsheet underlies the sections of said topsheet folded onto said bottom surface of said core and extends outwards beyond said side edges of said core; said sections of said topsheet folded onto said bottom surface of said core are bonded to said backsheet along zones extending, inside said lateral surfaces of said core, in parallel to a center line dividing a width of the diaper in two halves; and said elastic members associated with the leg-openings are bonded to said backsheet in vicinity of said side edges of said core.

2. A disposable diaper according to Claim 1 wherein said elastic members associated with the leg-openings respectively lie in said crotch region of the diaper within a range corresponding to a width defined by 10 mm as measured inwardly from said side edges of said core plus 30 mm as measured outwardly from said side edges.
3. A disposable diaper according to Claim 1, wherein said backsheet is formed on an inner surface thereof with a pair of barrier cuffs each having a relatively deformable distal edge extending longitudinally of said diaper inside each of said side edges of said core, a proximal edge fixed to said inner surface of said backsheet outside or inside said side edge of said core and extending in parallel to said distal edge, and an elastic member secured to said distal edge along an apex thereof under tension given longitudinally of said diaper so that said barrier cuff is normally biased by said tension to rise on said inner surface of said backsheet.




FIG.2




FIG.3






FIG. 5





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

DOCUMENTS CONSIDERED TO BE RELEVANT			EP 99303059.2
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 6)
A	EP 0781539 A2 (UNI-CHARM CORPORATION) 02 July 1997, claim, figs., column 2, lines 52-55, column 3, lines 12-15. --	1-3	A 61 F 13/15
A	US 5458592 A (ABUTO) 17 October 1995, claims, figs. 1-4, column 2, lines 63-66, column 5, lines 3-48, column 6, lines 15-67. --	1	
A	US 5520673 A (YARBROUGH) 28 May 1996, abstract, figs., column 1, lines 34-40, column 4, lines 16-33, column 6, lines 15-54, column 15, lines 53-64. --	1-3	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 6)
A	EP 0593082 A1 (UNI-CHARM CORPORATION) 20 April 1994, claim, figs. ----	1-3	A 61 F A 61 L
The present search report has been drawn up for all claims			
Place of search VIENNA		Date of completion of the search 27-07-1999	Examiner SCHÄFER
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (01.01.97)

BEST AVAILABLE COPY

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO. EP 99303059.2**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned search report.
The members are as contained in the EPIDOS INPADOC file on 30. 7.1999.
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP	A2	781539	02-07-1997	AU A1 71978/96	05-06-1997
				AU B2 706066	10-06-1999
				BR A 9604629	23-05-1998
				CA AA 2191368	31-05-1997
				EP A3 781539	03-02-1999
				JP A2 9149916	10-06-1997
				US A 5800419	01-09-1998
US	A	5458392	17-10-1995	AU B2 698657	05-11-1998
				NO A1 9707761	06-03-1997
				AU A1 3417795	19-03-1997
				CA AA 2225467	06-03-1997
				EP A1 847263	17-06-1998
US	A	5520673	28-05-1996	CA AA 2136249	25-11-1998
EP	A1	593082		none	

For more details about this annex see Official Journal of the European Patent Office, No. 12/82.

BEST AVAILABLE COPY